



Specification:
 *Electrical Characteristics:
 Current Rating:1.5A.
 Withstanding Voltage:AC500V r.m.s.
 Insulation Resistance:1000Megohms Minimum at DC 500V
 Contact Resistance:100Milliohms Maximum.
 *Mechanical Characteristics:
 Mating Cycles:5000 Insertions.
 *Environment:
 Operating Temperature:-40To+60

| CONNECTOR TERMINAL NO | PIN NO |
|-----------------------|------------------------------|
| PIN 1 | VCC:PWR SIGNAL AND GND |
| PIN 2 | RST:RESET SIGNAL |
| PIN 3 | CLK:CLOCKING SIGNAL |
| PIN 5 | GND:PWR SIGNAL AND GND |
| PIN 6 | VPP:PROGRAMMING VOLTAGE |
| PIN 7 | I/O:SERIAL DATA INPUT/OUTPUT |

| GENERAL TOLERANCE | DWG NO. |
|-------------------|-----------|
| X.±0.25 | X.±5° |
| X.±0.20 | X.±2° |
| .XX±0.15 | .XX±1° |
| .XXX±0.08 | .xxx±0.5° |
| SHEET 1/1 | |

| APPD: | WIND | Scale |
|-------|------------|-------|
| CHKD: | | 1:1 |
| DR: | | mm |
| Date | 2012/12/31 | |

MARK-SIM05-140-0014
 SIM CARD PUSH PUSH
 6P (顺向)
 深圳市迈瑞康电子有限公司

| REV. | EGN.NO. | MODIFY CONTENT | DATE |
|------|---------|----------------|------------|
| A | | NEW | 2011/12/31 |