



- Note:
- Material:
 - Housing: High temperature thermoplastic with g.f, UL94V-0
 - Contact: copper alloy, t=0.20mm
 - Shell: copper alloy, t=0.25mm
 - Specification:
 - Current rating: 1 A Max. voltage: 100 V(ac) for 1 min.
 - Dielectric withstanding
 - Contact resistance: 50 mW Max.
 - Insulation resistance: 100 MW Min.
 - Total mating force: 3.57 Kgf Max.
 - Total unmating force: 1.0 Kgf Min. 0.81~2.05 Kgf Min.
 - Temperature range: -30°C~80°C

PART NO:		MATERIAL: SEE NOTE	
MODEL NO: XX		FINISH: SEE NOTE	
UNIT: MM	SIZE: A4	COLOR: SEE NOTE	
TOLERANCE UNSPECIFIED			
.x	0.15	DR: xiyayouhong	
.xx	0.10	CHK:	
.xxx	0.05	APP:	
Ang.	1°	SCALE: 5:1	DATE: 2012.05.21
TITLE: 深圳市迈瑞康电子有限公司		DWG NO: MRK-MU11-720-0038	REV: A
Micro used 5P/F B Type SMT DIP7.2 无导线长1.1四脚全插			

REV.	ECH NO	LOCATIONS	DESCRIPTION	DATE