



P.C.B LAYOUT
 BOTTOM VIEW

SPECIFICATIONS:

Contact current Rating:1Amperes.
 DIELECTRIC Withstanding Voltage:AC 500V
 at sea level
 Insulation resistance:1000Megohms

Contact Resistance:30Milliohms Maximum
 operating Temperature:-55~ ta+85~

MECHANICAL CHARACTERISTICS:

Mating Force:3.5Kg.Maximum
 Umating Force:1kg.Minimum.

MATERIALS:

CONTACTS:Copper Alloy.
 Insulator:Thermoplaste P.B.T.UL 34V-0

Shell:Brass t=0.30±0.02

Contact:GDLD

Shell:Nickel Plated.

序号	名称	数量	料号	材料	表面	备注
3	拔蕊	1		PBT 30MG		COLOR: BLACK/WHITE...
2	端子	4		C5191H	VIGRET PAINED OVER ALL 100% TOP GOLD PLATING	GDLD/1, 3, 5, 10, 15, 30d"
1	外壳	1		黄铜/Fe	NICKEL PLATING	

REV	变更说明	签名	日期	审核	日期	制图	DFU	产品名称	图号	张数
1-4								AF-180-13.7弯脚		1
1-3										1
1-2										1
1-1										1
MODIFICATION										
变更说明										
SIGNATURE										
DATE										
CHECKED										
DATE										
GENERAL TOP										
X. 13										
X. 13-1										
XX 13-8										
X. 22.0"										
X. 21.0"										
X. 20.0"										
DRAMA										
CHECKED										
APPROVAL										
角法										
PROJ.										
PRODUCT NAME										
PART NO										
MRK-US20-137-0022										
DWG NO										
9										

深圳市迈瑞康电子有限公司

AF-180-13.7弯脚

MRK-US20-137-0022

图号 9