



PCB.LAYOUT

特性: Specifications:

电器: Electrical:

接触阻抗: Contact Resistance

30 milliohms MAX

耐电压: Dielectric Withstanding Voltage:

500V AC AT Sea Level

绝缘阻抗: Insulation Resistance:

100 MEGA ohms MIN

材料: Material:

塑胶: PBT

端子: Contact: Copper Alloy C2680H

铜壳/铁壳: Shell: Copper Alloy C2680H/Spcc

电镀: Finish:

端子: Contact: Plated Gold in Mating Area;

Tin/ On Solder Tails

接触点镀金.脚镀锡

铜壳/铁壳: Shell:

Nickel Plating

镀镍

变更内容 Midify content	签名 Sign by	审核 Checked by	日期 Date	Unless otherwise specified tolerances are 未注尺寸公差		客户	编号	图号	设计	审核	批准	Third Angle Project 第三角投影		
				X	±0.3	Customer	MRK-US90-194-0028	Drawing NO.	Designed by	Checked by	Approved by			
				XX	±0.2	品名	USB AF 90° 侧插(长体)有塞带盖(C款)			装配图				
				XXX	±0.1	版本	材质	厚度	数量	表面处理	交期		单位	比例
				XXXX	±0.05	REV	Material	MAT. THICK	Amount				Unit	Scale
			XXXXX	±--										
				ANGLES ±2°	SURFACE TEXTURE	由 Autodesk 教育版产品制作			mm	FREE	深圳市迈瑞康电子有限公司			