



- Material:
 - Contaeis: Phosphone
 - Bronze
 - insulater: PBT+30%
 - G. F. UL 94V-0
 - Shell: SPCC
- Mechanical:
 - Mating: 35N max.
 - Withdrowa Force: 10N min.
 - Darability: 1500 cycles min.
- Elecetical:
 - Current-max (amps) 1.5A
 - Voitage-max (volts) 30V
 - Withstanding Voltage 750V AC
 - Contact Resistance (ohms) 30 milliohms max insulation
 - Resistance (ohms) 1000 Megogms min.
- Plating:
 - Contacts: Gold And Tin Over
 - Nickel Ploled
 - Shell: Nickel over all plating.
- Environmental:
 - temperature Range: -55 to 85

产品图

MANUFACTURE DWG

公差一览表

TOLERANCE UNLESS OTHERWISE

深圳市迈瑞康电子有限公司

MRK-US11
-240-0052

单位	MM	INCH
.X	±0.20	.X ±---
.XX	±0.10	.XX ±---
.XXX	±0.05	.XXX ±---

2014-08-05

产品名称

USB A/F 侧插短体无卷边0形脚

角法

制图

DRAWING

比例

1:1

设计

DESIGN

审核

CHKD

核准

APPD

版本

AI

图号

CKC1

张数

1/1