



规格说明: Specifications:
电气特性: Electrical:

- 1. 额定电流: Current Rating
1.5A/contact terminal
- 2. 额定电压: Voltage Rating
30V DC
- 3. 接触阻抗: Contact Resistance
30 milliohms MAX
- 4. 耐电压: Dielectric Withstanding Voltage:
500 V AC AT Sea Level
- 5. 绝缘阻抗: Insulation Resistance:
1000MEGA ohms MIN

物理性能: Mechanical:

- 1. 插拔力: Connector Mate and Umate Force
Mate force: 3.57kgf (MAX)
Umate force: 1.02kgf (MIN)
- 2. 端子保持力: Terminal Retention
1.2kgf (MIN)

原材料: Material:

- 1. 塑胶: Housing:
Hing Temperature Ternmaplastics,
UI 94V-0 PBT White/Black
- 2. 端子: Contact: Copper Alloy C2680
- 3. 外壳: Shell: Copper Alloy C2680/SPCC

电镀: Finish:

- 1. 端子: Contact: Plated Gold in Mating Area;
Tin On Solder Tails
- 2. 外壳: Shell:
Nickel Plating

深圳市迈瑞康电子有限公司

品名 (ITEM NO)	A/F 90°DIP短体鱼叉脚10.6	图号 (DWG NO)		单位 (UNIT):	MM
料号 (PART NO)	MR-U05095	版本 (REV)	A/0	比例 (SCALE):	1:1
型号 (MODEL NO)		日期 (DATE)	2011.07.09	公差 (TOLERANCE):	UNSPECIFIED
		设计		未注公差	±0.30
		审核			±0.20
		核准			±0.10
					±0.05
					±0.02